



**Designed for the budget-minded, the I series printers have the features needed to support many applications at an affordable price. With its all-metal construction, patented printing mechanics and reliable electronics, the rugged I series printer minimizes downtime and maintenance costs.**

**By using the buttons and the 3 line graphical LCD on the front panel, users can set up, configure and fine tune printing parameters without having to send commands through the host.**

**Embedded Real Time Clock/Calendar enables printing accurate time and date on labels. Optional heavy duty rotary cutter and external label rewinder extend the application of the I series printers to an even wider range.**

### **Perfect for:**

- Inventory management
- Manufacturing
- Compliance labeling
- Shipping/Receiving
- Product ID

## POSTEK I-200 Series

### Industry Specifications

Model	I200
Printing Method	Direct thermal & Thermal transfer
Printing Resolution	200dpi(8dots/mm)
Max Printing Speed	6ips(152.4mm/s)
Max Printing Width	4.25" (108mm)
Max Printing Length	315"(8000mm)
Memory	4MB FLASH ROM, 16MB SDRAM
Media	Width: 4.56"(116mm) max, 0.79" (20 mm) min. Total thickness (including liner, if any): 0.0024"(0.06mm)~0.0098"(0.25mm). Supply roll: OD8"(203.2mm) max.. ID 1.5"(38mm) min.
Ribbon	Max width: 4.65"(118mm). Max length: 1968'(600m). Ink side: both In and Out. Ribbon roll: OD3.3"(84mm) max.. ID1"(25.4mm) min.
Fonts	User-download TrueType Fonts (Optional) Five built-in ASCII fonts
Bar Code Types	1D Barcode: Code 39, Code 93, Code 128/subset A,B,C, Codabar, Interleave 2 of 5, UPC A/E 2 and 5 add-on, EAN-13/8/128, UCC-128, Postnet, Plessey, HBIC, Telepen, FIM , etc; 2D Barcode: MaxiCode, PDF417, Data Matrix, QR, etc.
Media sensor	Reflective/Transmissive
Interfaces	RS-232 serial, USB.
LCD Display	Graphical
Power rating	110VAC±10%, 50/60Hz.
Weight	15kgs.
Dimensions	W11.3"(286mm) x D17.6"(448mm) x H11.0"(280mm).
Operating Environment	Temperature: 32°F–104°F(0°C – 40°C) Relative humidity: 5% - 85% non condensing
Optional Items	Cutter kit, External Rewinder.

**Remarks:** All specifications are subject to change without notice.